



TODO:

- ADD SNAP-ON FERRITE BEAD (SYMBOL) TO DRAWING - PER CURRENT INSTALL.
- AS REQUIRED: REMOVE RS232 WIRING FROM LOOM - DUE INCOMPATIBILITY BETWEEN MGL VOYAGER EFIS AND TQ KRT-2 RADIO.
- REMOVE AUDIO GROUND WIRE.
- REMOVE WIRE COLOURS.

FABRICATION NOTES:

- ISOLATE JACK SLEEVE (MOUNTING NUT AND PLATE) FROM AIRCRAFT CHASSIS.
- ALL STRANDED WIRE MUST CONFORM TO MIL-W-22759/16 OR EQUIVALENT. (SPEC 55)
 - ALL SHIELDED WIRE MUST CONFORM TO MIL-C-27500 OR EQUIVALENT.
 - WIRE SPEC:
TE RAYCHEM 55A0811
 - WIRE SIZES:
POWER(+) & POWER(-): 20 AWG (0.61 SQMM)
ALL OTHER WIRES: 22 AWG (0.32 SQMM) - TWISTED OR SCREENED AS INDICATED.

Sheet: /G-CBKY COMMS WIRING/
File: G-CBKY Comms Wiring.sch

Title: G-CBKY KRT2 COMMS WIRING

Size: A4 Date: 2018-06-24

KiCad E.D.A. kicad 4.0.2-stable

Rev: A

Id: 2/2